

## EMULSIONS/PRIMES

Emulsions are water-based products and are extremely sensitive to high shear and temperature fluctuations.

- Always roll a drum thoroughly before use.
- Never mix an anionic with a cationic base product.
- Always add water to an emulsion (not the other way around)
- Always check the compatibility of the water with an emulsion before diluting.
- Cationic emulsions should not be stored for long periods, use immediately after receipt.

### Winter recommendations:

- SprayPave Emulsions are temperature sensitive, and should be used shortly after receipt.
- Where possible, use during colder mornings/evenings should be avoided.
- Rolling a drum promotes good circulation of the product and binder prior to use.

Refer to the product technical data sheet for more product specific information.

## HOT BINDERS

Hot binders are bitumen-based products with an elastomer, plastomer or hydrocarbon additive.

- Always circulate before use.
- Never overheat product.
- Ensure that no water can get into this product.
- Never heat without agitation.

Refer to the product technical data sheet for more product specific information.

## PRECAUTIONS

### PRODUCT COLLECTED IN OWN HAULER/BIN/DRUM/CONTAINER

SprayPave's aim is to ensure that you as a customer is issued with a quality product every time. Quality is our main priority and a full life cycle assessment of the product is undertaken before it gets to the point of dispatch.

Should you wish to collect product in your own collection vessel kindly ensure the following:

- The vessel is clean and free of contaminants, soap solutions, degreasers.
- The vessel does not have any product that will affect the current product.
- The vessel is secure and cannot leak any product into the environment.
- In the case where the vessel is a hauler/tanker, the vessel has been flushed and no residue can contaminate, break, or cause any damage to the current product.

**Please note that SprayPave does not take any responsibility should the above not be adhered to or once the product has left the site.**



[ORDERS@SPRAYPAVE.CO.ZA](mailto:ORDERS@SPRAYPAVE.CO.ZA)



ISO 9001:2015 CERTIFIED



011 868 5451  
031 777 1905  
021 931 0459



[WWW.SPRAYPAVE.CO.ZA](http://WWW.SPRAYPAVE.CO.ZA)